

The Ganga Silk tank is an economical and a popular blow-moulded water storage tank, comprising of three layers: an enhanced aesthetic layer, UV protective sun-shield layer and an advanced anti-bacterial layer. These layers contribute to maintaining water quality, extending the tank's lifespan, and ensuring the safety and hygiene of stored water.



## Ganga Silk Tank

### Available Colour



White




**3 THREE LAYER**



### Salient Features:

- ▶ **Advanced Anti-Bacterial Layer:** Guarantees water purity and safety with an inner anti-bacterial layer, effectively preventing bacterial contamination.
- ▶ **UV-Protective Sun-Shield Layer:** Provides reliable protection against harmful UV rays, preserving water quality and integrity.
- ▶ **Enhanced Aesthetic Layer:** Crafted with high-quality raw material, with various colour options which add an aesthetic appeal to the tank.
- ▶ **Injection-Moulded Threaded Lid:** Features a robust injection-moulded threaded lid for secure sealing.
- ▶ Offered in sizes ranging from 500 to 2000 litres to accommodate various needs.
- ▶ **NSF/ANSI/CAN 61:** Certified by IAPMO under NSF/ANSI/ CAN 61 standards, providing additional quality assurance and peace of mind.

**Note:** Availability of colours may vary by region.



Cross-section of "Ganga Silk 3 Layer" water tank



- Enhanced Aesthetic Layer
- UV-Protective Sun-Shield Layer
- Advanced Anti-Bacterial Layer

### SPECIFICATION

Capacity (Ltrs.)	Overall Diameter (mm)	Height (mm)	Manhole Dia (mm)
500	860	940	380
750	960	1090	380
1000	1050	1220	380
1500	1220	1480	390
2000	1335	1630	390

Loft tanks are specifically designed and manufactured for both indoor & outdoor purposes. They are rectangular in shape and can be easily accommodated in kitchens, rooftops, balconies and other spaces efficiently.



## Ganga Loft Tank

### Available Colour



White



### Salient Features:

- ▶ High-quality raw material
- ▶ Stylish design
- ▶ Versatile and multipurpose usage
- ▶ Ideal for small spaces
- ▶ Available in a three-layer configuration

### SPECIFICATION

Capacity (Ltrs.)	Length (mm)	Width (mm)	Height (mm)	Manhole Dia (mm)
100	785	490	320	296
150	900	560	365	296
200	980	610	393	296
300	1200	750	400	296
400	1350	840	420	296
500	1470	950	426	350
1000	1945	1260	500	350

\*There could be variations in specifications and colors due to continuous product development. All sizes and capacities are approximate.