ISI Tank

ISI is a superior quality rotational moulded water tank conforming to IS 12701:1996. Polyethylene (PE) of rotational moulded grade, which is duly stabilized with antioxidants, is used as the raw material for manufacturing the tank. The compound hence formed provides protection against heat and oxidation of tanks. The nominal service temperature of Vectus ISI tanks varies from 1°C to 50°C.




Salient Features:

- **Premium Raw Materials:** Crafted from high-quality raw materials, ensuring superior quality and purity of stored water.
- **Heat and Oxidation-Resistant Construction:** Engineered with heat and oxidation-resistant materials, guaranteeing durability and longevity even in harsh environments.
- **Smooth Surface Finish:** Boasts a smooth surface finish, facilitating easy cleaning and maintenance
- **Heavy-Duty Lid:** Features a robust lid for enhanced durability and secure sealing, guaranteeing long-lasting performance.
- **Wide Range of Sizes:** Available in a wide range of sizes, from 200 to 10,000 litres, catering to diverse capacity needs and ensuring there's an option suitable for every requirement.

SPECIFICATION

Capacity (Ltrs.)	Overall Diameter (mm)	Height (mm)	Manhole Dia (mm)
200	742	560	280
300	761	770	280
500	905	1000	400
700	1020	1045	400
1000	1127	1230	400
1500	1320	1410	400
2000	1400	1610	390
3000	1550	1800	460
5000	1900	2050	460
10000	2045	2800	460



*There could be variations in specifications and colors due to continuous product development. All sizes and capacities are approximate.